

# OR-1602S


1.6m Eco Solvent Printer (With 2 i3200-E1 Heads)



ORIC Eco Solvent Ink



Two i3200-E1 Heads




\* 1.6m Dual i3200-E1 Print Heads Speed

720x1200dpi - 4pass	40 m <sup>2</sup> /h
720x1800dpi - 6pass	27 m <sup>2</sup> /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.



Intelligent inkjet printing technology and variable dot ensure the perfect printing output, greatly improve the printing speed, and meet the user's requirements for printing quality and speed.



High speed micro piezoelectric inkjet printing technology OR1602S is equipped with dual i3200 print heads. It adopts advanced board control technology and industrial level design to ensure the durability of the print head .



## ● Technical Specifications


<b>Model</b>	<b>OR-1602S</b>
<b>Print Head</b>	Dual i3200-E1 Print Heads
<b>Printing Technology</b>	Piezoelectric Inkjet
<b>Acceptable Media</b>	Width 63.8 in.(1620 mm) Thickness Maximum 39 mil(1 mm) Weight 132.2 lb.(60 kg)
<b>Printing Width</b>	63 in.(1600 mm)
<b>Ink Cartridges</b>	Type Eco Solvent Ink Capacity 4*4 CISS (220ml ink cartridge with 1.5L ink tank) Color 4 colors (Cyan, Magenta, Yellow, Black)
<b>Printing Resolution</b>	Maximum 2400 dpi
<b>Printing Speed</b>	4pass(720x1200dpi): 40sqm/h 6pass(720x1800dpi): 27 sqm/h
<b>Media Heating System</b>	Integrated post heater & Infrared Dryer & Fan system
<b>Interface</b>	LAN
<b>Power Supply</b>	AC 220V ± 10%, 50/60 HZ
<b>Dimensions(with stand)</b>	119(W)x41(D)x56(H) in. ( 3010(W)x1048(D)x1420(H) mm )
<b>Weight(with stand)</b>	661 lb. (300 kg)
<b>Package Dimensions</b>	124(W)x41(D)x59(H) in. ( 3140(W)x1048(D)x1490(H) mm )
<b>Package Weight</b>	771 lb. (350 kg)
<b>Environment</b>	Power on Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] (68 ℉ [20 ℃] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation)
<b>Accessories</b>	Dual I3200 Print Heads, USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.



THK high-precision mute rail.



New pinch roller structure of three in group brings more stable feeding precision.



High-precision and high-stability tensioning pulley system.



High quality DC servo motor with good stability and long life.



Stable Bulk System Ensures Amazing Printing Speed



Infrared heater and cooling fan.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



External power supply, intelligent rolling system