

OR-18045 / OR-32045


Eco Solvent Printer (With 4 I3200-E1 Heads)



ORIC Eco Solvent Ink



Four I3200-E1 Heads



* 1.8m Four I3200-E1 Print Heads Speed

360x2400dpi - 4pass	84 m ² /h
720x1800dpi - 6pass	62 m ² /h
720x2400dpi - 8pass	47 m ² /h

* 3.2m Four I3200-E1 Print Heads Speed

360x2400dpi - 4pass	100 m ² /h
720x1800dpi - 6pass	85 m ² /h
720x2400dpi - 8pass	70 m ² /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.



● Technical Specifications

Model	OR-1804S	OR-3204S
Print Head	Four I3200-E1 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	71.6 in.(1820 mm)
	Thickness	Maximum 59 mil(1.5 mm)
Weight	Weight	132.2 lb.(60 kg)
	Printing Width	70.8 in.(1800 mm)
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank)
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 2400 dpi	
Printing Speed	4pass(360x2400dpi) :	84 sqm/h
	6pass(720x1800dpi) :	62 sqm/h
	8pass(720x2400dpi) :	47 sqm/h
Media Heating System	Integrated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0 / LAN	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	125.3(W)x38.1(D)x54.5(H) in.	180(W)x38(D)x62(H) in.
	(3213(W)x970(D)x1388(H) mm)	(4580(W)x970(D)x1580(H) mm)
Weight(with stand)	882 lb. (400 kg)	2204 lb. (1000 kg)
	132.8(W)x39.8(D)x62.3(H) in.	194(W)x44(D)x71(H) in.
Package Dimensions	(3380(W)x1010(D)x1600(H) mm)	(4940(W)x1130(D)x1810(H) mm)
	Package Weight	1102 lb.(500 kg)
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



THK high-precision mute rail.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



High-precision and high-stability tensioning pulley system.



New independently adjustable three-stage pinch roller brings more stable feeding precision.



Increase the bottom heating of the carriage which can improve printing stability.



Bulky ink bottle with lack of ink alarm system represents the advanced concept of industrial application.



Dual integrated IR & cooling fan system,meet the drying needs of high-speed printing.



New high quality DC servo motor with good stability and long life.