



OR-3200UV PRO

High Speed UV Roll to Roll Printer (Gen5 / Gen6 optional)





ORIC UV Ink










































OR-3200UV Pro (V)



OR-3200UV Pro (S)



OR-3200UV Pro (Q)



Wide applications in light box, soft film, 3P fabric, scraping fabric, vinyl, light film, wallpaper, wall fabric, canvas, silk fabric, leather and etc.

6 Gen5 print heads arrangement (CMYK):

o Gens print neads arrangement (CMTK).				
Front Light 600x600dpi	67 m²/h			
Front Light 600x900dpi	45 m²/h			
Backlit 600x900dpi	33 m²/h			
Backlit 600x1200dpi	28.6 m ² /h			

6 Gen6 print heads arrangement (CMYK):

Front Light 600x600dpi	87 m²/h
Front Light 600x900dpi	58 m²/h
Backlit 600x900dpi	43 m ² /h
Backlit 600x1200dpi	37 m²/h

Technical Specifications


Model		OR-3200UV Pro (V)	OR-3200UV Pro (S)	OR-3200UV Pro (Q)	
Print Head		Four Industrial Heads	Five Industrial Heads	Six Industrial Heads	
Printing Resolution		300dpi、600dpi、900dpi、1200dpi			
	Width	210-3250 mm			
Acceptable Media	Thickness	Maximum 0.039 mil (1 mm)			
	Diameter	Heavy-duty Media Feeding System has no limit for roll diameter of media			
		Economic Media Feeding System is suitable for roll media diameter less than 210mm			
	Weight	220 lb.(100 kg)			
Printing Width		210-3200mm			
	Туре	LED UV			
Ink	Capacity	Continual Ink Supply System (1.5L ink tank)		
	Color	CMYK+W+Varnish	CMYK / CMYK+W / CMYK+W+CMYK	CMYK	
Ink Curing Unit		Dual UV LED Lamps			
Printing Resolution Maximum 1200 dpi					
Interface USB 2.0					
Power Supply AC 220V ±5 %, 16A, 50Hz ±1					
Dimensions(with stand)		213(W)x47(D)x62(H) in.5410(W)x1200(D)x1570(H) mm			
Weight(with stand)		1200 kg			
Package Dimensions		222(W)x45(D)x71(H) in.5650(W)x1150(D)x1800(H) mm			
Package Weight		1700 kg			
Environment	Power on	Temperature: 59 $\mathbb F$ to 90 $\mathbb F$ [15]	C to 32 C] / Humidity: 35 to 80% (no co	ondensation)	
	Power off	Temperature: 41 $\mathbb F$ to 104 $\mathbb F$ [5 $\mathbb C$ to 40 $\mathbb C$] / Humidity: 20 to 80% (no condensation)			

- High-efficiency UV LED technology;
- Environmentally friendly UV ink meets international environment standards;
- Industrial-grade structure, easy to operate, high stability;
- Upgraded dual guide rails ensure more stable printing;
- The media system with torque motor and air-shaft makes more stable rolling media;
- Equipped soft film tension system offers suitable pressure for various media.

With LED UV curing technology, OR-3200UV Pro is one of the most competitive UV roll to roll printers which characterizes with excellent quality, high stability and easy operation. OR-3200UVL enables to make high quality design in the most cost-effective way

Maximum 6 Ricoh Gen5/G6 print heads

Three lines print heads in staggered layout makes the highest productivity and various applications with optional CMYK, W+CMYK, CMYK+W, CMYK+W+CMYK (three layers) and W+CMYK+V (three layers) color modes.









More stable upgraded media feeding system



New designs including adjustable air-driven pinch roller system, upgraded media roller surface and feed motor control system ensure stability of media feeding.

NEW soft film feeding system

Air-driven moisture system, pinch roller and soft film feeding system





