

OR18-TX4 PRO


High Speed Sublimation Printer (With 4 Heads)



ORIC Sublimation Ink



Four I3200 Heads
CMYK



* 1.8m Four I3200 Print Heads Speed

360x1200dpi - 1pass	180 m ² /h
360x2400dpi - 2pass	120 m ² /h
360x3600dpi - 3pass	90 m ² /h

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering: top performant, reliable and precise. With ORIC series printer, you can maximize production while controlling quality and minimizing costs for beautiful soft signage, apparel and interior decor items that will set your business apart from the competition. Wide applications in clothing, home decoration fabrics, sampling, shirt, canvas bags, bolster, scooter, flags, textile gadgets etc.



● **Technical Specifications**

Model	OR18-TX4 Pro	
Print Head	Four I3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	72 in.(1830 mm)
	Thickness	Maximum 39 mil(1 mm)
Printing Width	Weight	≤ 800m
	Width	70.8 in.(1800 mm)
Ink Cartridges	Type	Dye Sublimation Ink
	Capacity	4*4 CISS
Printing Resolution	Color	4 colors (Cyan, Magenta, Yellow, Black)
	Resolution	Maximum 3600 dpi
Printing Speed	2pass(360x1200dpi):	180 sqm/h
	3pass(360x1800dpi):	120 sqm/h
	4pass(360x2400dpi):	90 sqm/h
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	LAN	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	125(W)x38(D)x56(H) in.	
	(3213(W)x970(D)x1420(H) mm)	
Weight(with stand)	1212 lb. (550 kg)	
Package Dimensions	135(W)x42.5(D)x62.5(H) in.	
	(3440(W)x1080(D)x1590(H) mm)	
Package Weight	1322 lb. (600 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] (68 ℉ [20 ℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	




New pinch roller structure of three in group brings more stable feeding precision



Stable bulk system ensures amazing printing speed.



THK high-precision mute rail.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.




Rear loading and take-up to facilitate workflow.



Integrated IR & cooling fan system.



Front expander ensure quick and accurate take-up in high speed printing.



Junbo media roll maximum 800m media load.